

## GSRB Series Multipurpose Electric Ceiling Mount



### Key Features

- \* Extension range: 300-450mm
- \* Power supply: 220V AC / 2 x 16A output, 2 x DMX512 signal outputs
- \* Control options: Dry contact, RF, RS485
- \* Operation: Low-speed motorized movement
- \* Raise/lower: Push-button operation
- \* Limit settings: Multiple electronic upper and lower limits, easily adjustable
- \* Safety feature: Interlocking after the square tube is inserted, prohibiting upward and downward movement

The electric retractable lighting suspension rod is designed for temporary mounting of stage lighting equipment. Ideal for spaces with scattered mounting points, limited ceiling height, or low clearance.

Commonly used in venues such as conference centers, banquet halls, wedding venues, fashion runways, exhibition halls, press rooms, and small to medium-sized meeting rooms. All drive mechanisms and control systems are housed within the rod, ensuring smooth, reliable operation with a clean, professional appearance. Built for safety, durability, and long-term performance.

### Product Specifications Table

Model	Equipment dimensions(mm) (DxWxH)	Maximum load capacity (kg)	Maximum telescopic range (mm)	Ceiling Opening Dimensions (mm)	Net weight (kg)
GSRB-3003	165 × 242 × 701	500	300	φ175	10
GSRB-3004	165 × 242 × 830	500	450	φ175	12

