

## GPAD/AC 64 Series Dual Telescopic Rod Projector Lifter

Supports  
projectors up to  
**40KGS**



GPAD 64

### Product Features

#### Linear Shaft and Slider Transmission Assembly



The linear shaft and slider assembly ensures a smooth, stable lift without any vibration.

#### Electromagnetic Brake AC Motor



Equipped with an electromagnetic brake AC motor, delivering safe and reliable braking with noise levels below 55dB.

#### Anti-Fall Safety Device



The anti-fall protection system prevents the projector from dropping in case of any malfunction.

#### Proprietary Cable Extension Patent



The patented telescopic rod design integrates multiple power and signal cables, each guided by individual tension springs for synchronized and orderly extension.


## Main Features

- \* Featuring a single-pole telescopic design, most 20,000-lumen industrial projector
- \* Multi-section aluminum alloy square tubes with double-opening inner doors
- \* GPAC's projector cage can connect to decorative ceiling panels matching the ceiling material
- \* Patented cable management system
- \* Lifting without load-bearing
- \* Multiple protective anti-drop devices
- \* Fully enclosed aluminum alloy frame, durable and strong
- \* Industrial-grade long-running motor
- \* High-precision encoder, positioning accuracy  $\leq 1\text{mm}$
- \* Projector universal mounting claws, adjustable at multiple angles
- \* Built-in cables: Projector power cable  $\times 1$ , HDMI2.0  $\times 1$ , Cat6 network cable  $\times 2$
- \* Positioning methods: RF positioning and 485 positioning
- \* Control methods: RF, low-voltage dry contact, and RS485 encoding





GPAC

## GPAC Performance Overview



## GPAD Performance Overview



## Product Specifications Table

Model	Equipment Dimensions (mm) (DxWxH)	Compatible Projector Size (including cable and lens) (DxWxH)	Decorative Frame (mm)	Ceiling Opening Dimensions(mm) (DxW)	Ceiling Installation Space Required (mm)	Maximum Telescopic Travel (mm)	Net weight (kg)
GPAD6405/GPAC6405	975x825x750	730x620x280	1015x867	990x840	>800	500	100
GPAD6410/GPAC6410	975x825x875	730x620x280	1015x867	990x840	>925	1000	120
GPAD6415/GPAC6415	975x825x1000	730x620x280	1015x867	990x840	>1050	<b>1500</b>	125
GPAD6420/GPAC6420	975x825x1125	730x620x280	1015x867	990x840	>1175	2000	130
GPAD6425/GPAC6425	975x825x1250	730x620x280	1015x867	990x840	>1300	2500	135
GPAD6430/GPAC6430	975x825x1375	730x620x280	1015x867	990x840	>1425	3000	140
GPAD6435/GPAC6435	975x825x1500	730x620x280	1015x867	990x840	>1500	3500	145

## GUANGZHOU GRANDVIEW CREATIVE TECHNOLOGY CO., LTD

A: No.1 Building of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou China.

T: 86-20-84899499 F: 86-20-84805299

W: [www.grandviewscreen.com](http://www.grandviewscreen.com)



Grandview  
website