

Integrated Dual-Chain Transmission Hoist Load Capacity: 500KG

This hoist is designed for suspending heavy audiovisual equipment, such as line array speakers, flat-panel displays, and advertising lightboxes. It includes multiple audio/video signal cables and high-power electrical cables. The hoist supports wireless remote control and features an RS485 central control interface. Its dual-chain synchronized winch structure prevents rotation, and it includes multiple limit adjustments for precise control.

Compatible Cables:

- Cat 6 Ethernet cable
- AV audio cable
- Speaker cable
- 220V power cable



Precision Helical Gear Drive Mechanism

Equipped with a precision helical gear drive mechanism and a bidirectional chain output system, it ensures smooth operation with noise levels as low as 68 decibels even under full load.

Brake System

Heavy-duty DC electromagnetic brake, ensuring safety and durability.

Control Options

Supports low-voltage dry contact and RS485 control.

Anti-Drop Mechanism

The hoist features an internal anti-drop mechanism for enhanced safety.

Encoder

The built-in encoder allows for custom travel limit settings.

GUANGZHOU GRANDVIEW CREATIVE TECHNOLOGY CO., LTD

A: No.1 Building of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou China.

T: 86-20-84899499 F: 86-20-84805299

W: www.grandviewscreen.com



Grandview
website