

GPSC Series X-Arm Electric Projector Lift



Retracted Appearance



GPSC 5010B

Product Features


- * The ultra-thin electric lift uses an X-shaped composite arm with two high-strength, flame-retardant fabric belts, ensuring smooth and stable operation under load.
- * The frame is made from high-strength aluminum and covered with a painted sheet metal, isolating the projector from its surroundings for full protection.
- * Hidden installation design that blends seamlessly with the ceiling when retracted.
- * Equipped with electronic position control and one-click setup for easy operation.
- * Includes Graffiti IoT connectivity, enabling voice control via AI speakers.
- * Supports dry contact, RS-485, wireless remote control, and both wired and wireless trigger control.




Gear-Hinged Joint



Separate Projector Mount



Vertical Adjustment of Mounting Bracket



Built-in Cable Storage Clips

Product Specifications Table

Model	Equipment Dimensions (DxWxH) mm	Maximum load capacity (kg)	Maximum Travel (mm)	Net weight (kg)	Compatible Projector Size (including cable and lens) (W×H×D)mm	Ceiling Opening Dimensions (D×W×H)mm
GPSC 5005B	580×580×225	15	500	23.8	440x180x480	600x600
GPSC 5010B	580×580×225	12	1000	27.2	440x180x480	600x600
GPSC 5015B	580×580×340	10	1500	28.6	440x180x480	600x600

